



Submersible Single Channel Pumps

RSM Series



Remko heavy-duty wastewater and sewage pumps are engineered for extreme durability and reliability, this combined with their outstanding quality makes them ideal for the most demanding applications.

Each pump has been through stringent quality, precision and performance testing throughout production resulting in a superior line of pumps that you can trust.

Max Head: 40 m

Max Flow: 496 l/sec

RSM.100.75



SPECIFICATIONS

Pump Model	Outlet (mm)	Power (kW)	Amps (415 volt)	Speed (rpm)	Solids Passage (mm)	Weight (kg)
RSM.100.55	100	5.5	11.1	1440	40	146
RSM.100.75	100	7.5	15.2	1440	40	163
RSM.150.75	150	7.5	15.2	1440	70	230
RSM.150.110	150	11	21.2	1440	70	263
RSM.150.150	150	15	31	1440	76	194
RSM.150.220	150	22	39	1440	76	251
RSM.200.110	200	11	21.2	1440	75	277
RSM.200.150	200	15	26.2	1440	75	285
RSM.200.220	200	22	40	1440	76	327
RSM.250.220	250	22	40	1440	60	745
RSM.250.300	250	30	62	1440	60	765
RSM.250.370	250	37	75	1440	60	770
RSM.350.220	350	22	43	970	120	950
RSM.350.300	350	30	68	970	120	965
RSM.400.370	400	37	74	970	120	965
RSM.400.450	400	45	84	970	120	970



Single Channel Pump

For demanding municipal, commercial or industrial wastewater applications



RSM.400.450



RSM.150.75

INDUSTRIAL
COMMERCIAL
MUNICIPAL
SEWAGE
STORMWATER
TRADEWASTE

PERFORMANCE CURVES

